



PLANETARY GEARBOX GPL042



		1-STAGE	2-STAGE	3-STAGE		
Ratio i:1	Max. motor shaft-ØD		Ratio i:1	Max. motor shaft-ØD	Ratio i:1	Max. motor shaft-ØD
					49	8
				56	8	
		12.25	8	64	8	
		14	8	70	8	
		16	8	80	8	
		20	8	100	8	
		24	8	120	8	
		25	6	144	8	
		3.5	8	30	6	184
4	8	30.67	8	235.11	8	
5	6	38.33	6	293.89	6	
6	4	46	4	352.67	4	
7.67	3	58.78	3	450.63	3	

Standard scope of delivery Gearbox lubricated for duration of service life, dust-proof package, motor pinion, mounting screws, paper gasket and assembly instructions (adapter plate optional).

Customized versions also available for small quantities.

Stainless steel version on request.

Rated torque continuous	Type Standard	Type R	Nm	0.7	4	12
Rated torque intermittent	Type Standard	Type R	Nm	1.4	8	24
Rated torque continuous	Type V	Type S	Nm	1.4	8	12
Rated torque intermittent	Type V	Type S	Nm	3	12	24
Max. efficiency at rated torque			%	90	85	80
Average backlash at no load	Type Standard	Type V	arcmin ≤	20	35	50
Average backlash at no load	Type R		arcmin ≤	12	20	30
Average backlash at no load	Type S		arcmin ≤	8	12	15
Weight without adapter plate			g	275	350	425
Dimension L			mm	35	47.5	60
Dimension A			mm		7.5	
Dimension B			mm		20.5	
Max. radial load	F _R	9.5 mm from shaft end	N		150	
Max. axial load	F _A		N		120	
Max. continuous rated speed at drive			min ⁻¹		5000	
Max. intermittent rated speed at drive			min ⁻¹		8000	
Temperature range			°C		-25 / +90	

Type V = heavy duty version | Type R = reduced backlash version | Type S = low backlash version

Changes reserved © GYSIN AG | 10/2014